


Rigid Coupling



Nominal Size mm/in	Pipe O.D. mm/in	Working Pressure PSI/MPa	Bolt Size	Dimensions mm/in		
			No.-Size mm	Ø	L	H
25 1	33.7 1.327	500 3.45	2-M10x45	60 2.362	102 4.016	45 1.772
32 1¼	42.4 1.669	500 3.45	2-M10x45	70 2.756	106 4.173	44 1.732
40 1½	48.3 1.900	500 3.45	2-M10x45	73 2.874	108 4.252	44 1.732
50 2	57.0 2.245	500 3.45	2-M10x55	83 3.268	122 4.803	45 1.772
50 2	60.3 2.375	500 3.45	2-M10x55	87 3.425	123 4.843	44 1.732
65 2½	73.0 2.875	500 3.45	2-M10x55	100 3.937	138 5.433	44 1.732
65 2½	76.1 3.000	500 3.45	2-M10x55	103 4.055	142 5.591	45 1.772
80 3	88.9 3.500	500 3.45	2-M12x60	117 4.606	166 6.535	45 1.772
100 4	108.0 4.250	500 3.45	2-M12x65	137 5.393	188 7.401	48 1.889
100 4	114.3 4.500	500 3.45	2-M12x65	139 5.472	190 7.480	49 1.929
125 5	133.0 5.250	400 2.75	2-M12x75	163 6.417	210 8.268	49 1.929
125 5	139.7 5.500	400 2.75	2-M12x75	168 6.614	218 8.583	49 1.929
150 6	159.0 6.250	400 2.75	2-M12x75	192 7.559	242 9.528	49 1.929
150 6	165.1 6.500	400 2.75	2-M12x75	193 7.598	241 9.488	49 1.929
150 6	168.3 6.625	400 2.75	2-M12x75	198.5 7.815	249 9.803	50 1.969
200 8	219.1 8.625	300 2.07	2-M16x85	253 9.961	320 12.598	59 2.323
250 10	273 10.748	300 2.07	2-M22x130	335 13.189	426 16.772	68 2.677
300 12	323.9 12.752	300 2.07	2-M22x130	380 14.96	470 18.504	65 2.559